

# ゼラストフィルム 鉄用

この製品は袋から発生する成分により錆の発生を防ぎます。  
本書をよくお読みいただき、正しくお使いいただきますようお願い申し上げます。

## 使用方法

- 防錆対象物を脱脂してから袋の中に入れてください。(油塗布などはしないでください。)
- 袋の中に入れた後は水分や外気が直接袋の中に入らないように、粘着テープ・シーラー等で封をしてください。(使用期限は購入日より3年以内です。封をしないと防錆期間・効果が著しく減少します。)

## △保管上の注意

- この製品は酸化性防錆フィルムのため、開封後はできるだけ早くご使用ください。
- 開封後、ご使用にならない分は外装にて空気の流れが無いように密封してください。(密封しないと製品に入っている薬品が気化して、効果が著しく短くなる可能性があります。)
- 直射日光を避け、温度30℃以下・湿度50%以下の冷暗所で保管してください。(温度が高い場所での保管は気化量が増え、防錆期間が大幅に短縮されます。)
- ゼラストフィルムの特性上、防錆成分や経過時間、保管温度などの影響で色調が変化することがありますが、防錆効果に影響はありません。

## △使用上の注意

- この製品は鉄用となります。
- 防錆対象物に水分・油分などの汚れの付着が無いように脱脂してください。
- 袋の中へ入れる際は防錆対象物を素手で触らないように手袋を着用してください。(手汗等が錆の原因となります。)
- 袋の中に入れた後は水分や外気が直接袋の中に入らないように、粘着テープ・シーラー等で封をしてください。
- 防錆対象物を梱包する場合は、ゼラスト袋に入れてから梱包してください。紙、ダンボール、発泡スチロールなどの緩衝材に対象物が直接接触すると、接触部から錆が発生します。
- 用途以外のご使用はおやめください。

購入日を書いて保管してください。

年 月 日

使用期限：購入日より3年以内

(推奨保管環境：温度30℃・湿度50%以下の冷暗所)

開封後、ご使用にならない分は外装にて密封して保管してください。

発売元  新潟精機株式会社

〒955-0055 新潟県三条市塚野目5丁目3番14号

☎(0256)33-5502(代) FAX(0256)33-5528

URL <http://www.niigataseiki.co.jp>

# ZERUST Film for Ferrous Metals

ZERUST Film creates rust inhibiting environment inside bag to protect contents from corrosion. Please read and follow these directions thoroughly.

## How To Use

- Degrease item or component before placing in bag.  
(Make sure item does not have oil coating.)
- After item is placed in bag, seal well, such as with adhesive tape to prevent exposure to outside air. (Anti-rust properties will last three years from date of purchase. If not sealed, this period will be significantly reduced.)

## Storage Notes

- Use as soon as possible after opening; Anti-corrosion film is volatile.
- Re-seal package immediately to prevent exposure to air. If anti-rust chemicals are allowed to evaporate, the protection may be significantly reduced.
- Store at temperature below 30°C (85°F), Less than 50%RH, and out of direct sunlight.  
(Storage at higher temperatures will increase vaporization and significantly reduce anti-rust protection period.)
- During storage, the ZERUST Film color may change dependent on storage time and temperature. Color change does not affect the anti-corrosive properties.

## Precautions

- For ferrous items. (Iron and Steel.)
- Clean and degrease to remove all dirt, moisture, and contamination from item to be stored.
- Handle item with gloves before placing into bag to prevent contamination with hand sweat and oils, which may cause rust.
- After placing item into bag, please seal with adhesive tape to prevent outside air from entering.
- Remove all packing and cushioning material from item before placing inside ZERUST bag. If item is in direct contact with cardboard, paper, Styrofoam, etc, rust may form at point of contact.
- Use only as directed.

 **Niigata seiki Co., Ltd.**

5-3-14, Tsukanome, Sanjo, Niigata, Japan, 955-0055  
Tel.: +81-256-33-5522 Fax.: +81-256-33-5518  
MAIL intl.sales@niigataseiki.co.jp  
URL <http://www.niigataseiki.co.jp>

Record Date of Purchase:

Year \_\_\_\_\_ Month \_\_\_\_\_ Day \_\_\_\_\_

- Expiration: 3 Years after date of purchase.  
(Rec. Storage:  $\leq 30^{\circ}\text{C}$  (85°F),  $\leq 50\%\text{RH}$ , dark)
- Keep unused product in sealed package.